

## ECK 4000-HFO BLACK LINE FOR HFO1234yf

**ECK-4000-HFO – Fully automatic A/C service station "full optional"** for recovery, recycling and recharging with the refrigerant HFO1234yf. The high refrigerant recovery rate ensures today's undeletable contribution to environmental protection.

**ECK-4000-HFO – Time savings during work processes**. The patented and very compact aluminium recovery unit makes the A/C service station unique and fast. Lines and distances are shortened thereby increasing efficiency and reliability. The working time is noticeably shorter, whereby the high working speed does not decrease even with high outside temperatures and very strong use. After the specification of all automatic or manual work steps by the operator, all processes are fully automated. No service valves need to be operated.

**ECK-4000-HFO – Environmentally friendly and cost saving**. All components and units are professional and strong. The internal tubes are made of copper and reduce refrigerant losses up to the technically possible minimum.

**ECK-4000-HFO – Additional comfort and security**. The 7" colour touch screen guarantees easy, intuitive and user-friendly menu navigation. The principle is a graphic representation of the procedures and selection of possible options with a short description. At any critical points, the operator is supported by a help function with direct answers. The menu navigation is something special in its user-friendliness and guides even inexperienced operators safely through the A/C service.

**ECK-4000-HFO - The patented hybrid function for electrically driven compressors** is a very efficient cleaning system for service couplings, service hoses and the internal lines. Thanks to this technology, the device can handle very cleanly the compressor oils of the A/C system in the vehicle. Even residual oil quantities between the hermetically and refillable containers and the oil injection valve in the device are eliminated.

**ECK-4000-HFO - Clean handling of compressor oil** of various standards and types. There are three hermetic and refillable containers for the respective refrigerant installed. The user is independent of the supplier, has a high level of user comfort, is future-oriented and excludes moisture absorption through hygroscopy of the oil media.

High-end in hardware, performance, function and userfriendliness in the "Black-Line" design. The most modern features are standard. This machine is the basis for the development of the specific ECK-4000 according to VDA.

**ECK-4000-HFO** - The pressure test with forming gas or nitrogen provides optimum security and is factory standard. The test gas is fed into the machine via a connection with a maximum pressure of 15 bar. Via a menu item in the software, the operator can check the vehicle A/C system in overpressure. The holding time and the threshold value for the pressure loss test are specified by the operator in the settings. After the check, the logging takes place and a report is printed out.

ECK-4000-HFO - Flexibility and upgrade with HFO1234yf gas identification. The machine can be upgraded within 10 minutes with our gas identification device, thus protecting the machine from contaminated refrigerants. This aims to reach advantages in safety, environmental protection and helps to avoid unexpected costs due to repair service of the contaminated machined. An increasing aspect for the investment in A/C service stations.

**ECK-4000-HFO - The workshop-oriented design** is user-friendly, space-saving, enables agile moving in the workshop and makes maintenance work on the machine very easy. The high-quality materials make the machine resistant to kicks and strikes.

**ECK-4000-HFO - Valuable and automated in any detail!** The compensation of the service hose length takes place automatically. Service couplings ("puff free") with dead space ventilation prevent refrigerant loss when releasing the service coupling and thus protect our environment. The pressure sensors can be calibrated automatically. The discharge of the "non-condensable" gases from the internal tank is automatic. The progress of the work flow is optically visible by the different colours of the status light and inform visually the operator.

**ECK-4000-HFO - Technology for the benefit of the workshop**. The special solution from Ecotechnics for the workshop of today and tomorrow. The fully equipped A/C service station with all the solutions to a safe and professional service with the refrigerant HFO1234yf.



## ECK 4000-HFO BLACK LINE FOR HF01234yf

High-end in hardware, performance, function and userfriendliness in the "Black-Line" design. The most modern features are standard. This machine is the basis for the development of the specific ECK-4000 according to VDA.

Type of refrigerant	R1234yf
Voltage	220-240V 50/60 Hz
Vacuum pump	100 l/min, vakuum level 0,1 mbar
Sealed compressor	1/3 HP
Recovery speed	300 g/min in liquid phase
Scale resolution	10 gr
Oil scale resolution	5 gr
Working temperature range	11/49 °C
Filter system	1 filter for humidity
Refrigerant tank	12 liters refillable
Hoses	3 meters
Puff free couplers	Standard
Service procedure	fully automatic or manual
Automatic service valves	Standard
Hybrid function / electrically driven compressors	Standard
Pressure test forming gas / nitrogen	Standard
Display	7" colour touchscreen
USB port	Standard
Thermal printer	Standard
Hermetic and refillable containers for oil and dye	Standard 2 + 1
Hermetic disposable containers for oil and dye	Option
Refillable standard containers for oil and dye	not available
Pressure guages	Class 1
Tank temperature sensor	Standard
Bottle heater	Standard
Automatic air purge	Standard
Dimension / weight	cm 55 x 60 x 110 kg 90
Dimension / weight with packaging	cm 70 x 70 x 130 kg 100



## STANDARD







STATUS LIGHT

## **OPTIONS**







