

RECOMMENDED ACCESSORIES

Safe and suitable solutions



Gas Analyser to handle the risk of contamination

- No external space necessary – integrated in the machine
- External Gas sample hose (not Service hoses!)
- Result gives % of refrigerant components
- Contamination of the station is excluded
- Easy to be installed (less than 20 minutes)

Most focussed selection of A/C compressor oil and dye

With just 3 standards, over 95% of market requirements are covered. Details in the catalog on page 30.

- Simple solution for the user
- Any product is “universal” for both HFO and R134a, mechanical and electric compressor
- Choice of bottles or hermetic cartridges
- Focussed on the most popular PAG and POE standards

Bottle	Cartridge	
AEK275	AEK275-N	Oil PAG100 - 250ml
AEK276	AEK276-N	Oil PAG46 - 250ml
AEK287	AEK287-N	Oil POE80 - 250ml
AEK386	AEK386-N	Oil + dye POE85 - 250ml
AEK290	AEL290-N	Dye - 250ml

Starterkit AEK006-2

The top recommendation for AC compressor oils and leak detection with UV light.

Diagnosis Sight Glass AEK232-2 for HFO1234yf or Diagnosis Sight Glass AEK232-1 for R134a

- Visual inspection of the refrigerant on the vehicle by running air conditioning system
- Visual inspection of the refrigerant when filling AC stations
- Use as a protective filter for AC stations in the case of unsafe vehicle AC systems.

HP Swift coupling AEK231-2 for HFO1234yf or AEK231-1 for R134a

HD extension couplings for e.g. BMW, Ford and Volvo, the solution when access to the HD service connections is difficult.

Manual injector AEK207A for R134a AEK207B for HFO1234yf

Fill compressor oil or dye manually via the LP connection by running AC system.

Flushing kit AEK102-N21 (neutral unit requires configuration)

- + AEK102-N21-1 Kit for HFO12324yf or
- + AEK102-N21-2 Kit for R134a

For cleaning the A/C system of components on the vehicle with refrigerant by an AC service station.

- Environmentally friendly because no solvents are used but only refrigerant
- Very efficient cleaning thanks to the high washing speed obtained with the vacuum in the tank
- Patented universal adapters for creating bypasses
- The amount of refrigerant can be defined by the user (washing a component rather than a system)
- Time-saving and efficiency thanks to the fast process and fully automatic cycles

Maintenance

KIT16	Maintenance Kit. Includes 1 bottle 500ml of vacuum pump oil + 1 filter FLT5005 x Cinquecento12, ECK LAND, ECK NEXT, ECK NEXT PRO, ECK 1900 PRO
KIT17	Maintenance Kit. Includes 1 bottle 500ml of vacuum pump oil PMP3335 + 1 filter FLT5512 x ECK FLAG, ECK 4012, ECK TWIN PRO
KIT18	Maintenance Kit. Includes 1 bottle 500ml of vacuum pump oil + 1 filter FLT5005 + 1 filter FLT5006 ECK BUS
FLT5512	Dryer filter 100 kg
FLT5005-KIT	Dryer filter 50 kg, 12 pc
PMP3335	Vacuum pump oil 500 ml ISO46
AUTOAGRI	Database update for car, truck and agriculture

DATA BASE
UPDATE